



Security Management System (SMS) Release Notes

Version 6.2.0.2

This release includes all issues fixed in the *Security Management System Release Notes Version 6.2.0* and *Security Management System Release Notes Version 6.2.0.1*. For details about those changes, refer to the respective Release Notes on the [Online Help Center](#).

Important notes for SMS

- All v6.2.0 customers can optionally apply this patch so that the issues it addresses are corrected. However, upgrades to a later TOS do not require an installation of this patch first.
- Patch installation should take approximately 15 minutes.
- To prevent your account from being disabled while you wait for authentication resources to become available after the reboot, navigate to **Edit > Preferences** and make sure that you deselect **Lock user after failed login attempts** and **Auto reconnect client to server after a disconnect occurs**. The SMS automatically reboots after you install this release. You will then be prompted to update the SMS client.
- This patch can be uninstalled or rolled back to the previous version.

Release contents

The following enhancements or repairs are included in this release.

Description	Reference
A Linux-based regreSSHion vulnerability (CVE-2024-6387) relating to a race condition that unauthenticated attackers could trigger through an OpenSSH server (sshd) has been addressed in this release.	VRTS-12508
An issue that prevented the Vertica log rotations from working has been fixed.	TIP-119177
The SMS no longer sends historical syslog entries after an upgrade or reboot.	PCT-15826 PCT-10500
This patch enables you to verify data integrity and detect data corruption by automatically logging a checksum whenever downloadable files are generated.	TIP-101070

Fixed an open file handle leak for Trend Vision One™ TLS Telemetry.	TIP-109599 TIP-111277 PCT-15707 PCT-16314
A condition that caused RADIUS authentication to fail intermittently has been repaired.	TIP-116312 PCT-18412
Port 443 must remain open for downloading installer applications from a web browser. When port 443 is enabled, the client UI will use it for downloading updates and patches during login; if this port is disabled, the client UI will fall back to java message Service (JMS) ports.	TIP-116410 PCT-20438
A condition that caused SNMP to fail has been fixed.	TIP-109752 PCT-20128
Geolocation IPs now continue to display correctly after an upgrade.	TIP-117156 PCT-20591
An SQL syntax error that affected SMS logins has been corrected.	TIP-109658 PCT-1996
Additional telemetry has been added for syslog diagnostics.	TIP-106815 TIP-117335 PCT-7954
Performance issues affecting SMS profile distributions have been repaired.	TIP-107299 PCT-2015
An issue that caused an internal error to be displayed on the SMS Web Console when attempting to display Suspicious Objects through the Trend Vision One account has been fixed.	TIP-116815 PCT-15707

Product support

For assistance, contact the [Technical Assistance Center \(TAC\)](#).